

## PA CONSOLE PANEL

### MODEL NO-PC-201



Agni protection PA console panel is for the purpose of making announcements, conveying information and messages needed in a particular location or zone. This finds, wide application in large areas like residential building, Hotels, Offices, Hospitals, Factories, commercial complexes, Airports, Education Institutions and Auditoriums. The consoles come in a range begins from 6 Zone Expandable up to 64 zones. This console is user friendly system with option of zone selection for individual zone announcement and common announcement through microphones.

This panel have facility for integration with fire alarm panel.

### Features and Benefits :

- Advance Micro controller based 6-64 zone PA console Panel
- Inbuilt amplifier as per requirement
- One Inbuilt Mike For announcement.
- Zone wise and common announcement facility.
- All call selection Facility.
- 100V Audio output for speaker.
- Modular design, plug in type solid state
- Keypad with feather touch switches for zone selection.
- Music player attachable facility (Optional)
- Mains, AC fail, fuse blown LED indication
- Inbuilt battery charger and battery space (up to 25AH)

+91-8527498960, 8527498961, 8527498962

sales@agniprotection.com, support@agniprotectionindia.com

www.agniprotection.com



**An ISO 9001-2008 Certified Co.**  
**AGNI PROTECTION PVT. LTD.**  
**DATASHEET**

### **TECHNICAL SPECIFICATION:**

Mains Voltage	220~230V AC
Frequency	50~60 Hz
Power Consumption	7 Watt/45 Watt (Normal/Fire)
Operating Voltage	24 V DC
Speaker O/P Supply	100 V AC

### **Initiating Device Circuits (Zone Circuit): - All Zones are Class B wiring**

Normal Operating Voltage	16-24 V DC
Alarm Current	15-30mA
Short Circuit Current	100 mA
Maximum Zone Resistance	220 ohms
Standby Current	200 mA

### **ENVIRONMENTAL INFORMATION:**

Operating Temperature	0° C to + 65° C
Operating Humidity	5 to 95% Relative Humidity (non- condensing)

### **MECHANICAL SPECIFICATION:**

Cabinet Type	CRCA With Powder Coated Finish
Colour	Off White/Black/Red
KnockOut	20mm
Dimension (WXHxD)	610 X780X230 mm
Weight without Battery	25 Kg (No Battery Fitted)

 +91-8527498960, 8527498961, 8527498962

 sales@agniprotection.com, support@agniprotectionindia.com

 [www.agniprotection.com](http://www.agniprotection.com)



An ISO 9001-2008 Certified Co.  
AGNI PROTECTION PVT. LTD.  
DATASHEET

### ORDERING INFORMATION:

MODEL NO	PACK QTY.	DIMESION (WXHXD) MM	WEIGHT
PC-201	1	610X780X230	25 KG

### APPROVED BY:

