

## An ISO 9001-2008 Certified Co. **AGNI PROTECTION PVT. LTD.**

## DATASHEET

## SPRINKLER ANNUNCATION PANEL **MODEL NO-SA-700**

This is microcontroller-based Sprinkler Annunciation or Annunciator panel which monitor 4 Zone up to 64 zones status and display the same in LED. It is designed to provide visual and audible indications of the status of sprinkler systems. Flow switch are Directly connected with the panel.

### **Features and Benefits:**

- As Per IS-15908:2011 Standard.
- Zone Wise annunciator Window for Zone status.
- Short Circuit/Overload Protection.
- Potential Free Contact Facility.
- Inbuilt Battery Charger & Battery Space. (2 Battery 12V 7Ah)
- Zone Healthy Indication.
- Compatible With all Make Flow Switches.
- Low Battery Visual Warning.
- Ex. Switch for Reset, Silence & Lamp Test.
- Relay O/P for common hooter.

#### **TECHNICAL SPECIFICATION:**

Mains Voltage 220~230V AC Frequency 50~60 Hz

**Power Consumption** 5 Watt/45 Watt (Normal/Fire)

Operating Voltage 24 V DC 24 V DC Detection O/P Supply Hooter O/P Supply 24 V DC 1

No of Relays

+91-8527498960, 8527498961, 8527498962

sales@agniprotection.com, support@agniprotectionindia.com

www.agniprotection.com



# An ISO 9001-2008 Certified Co. AGNI PROTECTION PVT. LTD.

## **DATASHEET**

## Initiating Device Circuits (Zone Circuit): - All Zones are Class B wiring

Normal Operating Voltage 16-24 V DC
Alarm Current 15-30mA
Short Circuit Current 100 mA
Maximum Zone Resistance 220 ohms
End of Line 4.7k
Standby Current 200 mA

### **ENVIRONMENTAL INFORMATION:**

Operating Temperature  $0^{\circ}$ C to + 65 $^{\circ}$ C

Operating Humidity 5 to 95% Relative Humidity (non-condensing)

#### **MECHANICAL INFORMATION:**

Cabinet Type CRCA With Powder Coated Finish

Colour Off White/Black/Red

KnockOut 20mm

Dimension (WXHXD) 400 x 320 x 130 MM (4-16 Zone)

600 x 400 x 155 MM (18-32 Zone)

Weight without Battery 5.6 KG (16 Zone)

9.5 KG (32 Zone)

#### **ORDERING INFORMATION:**

MODEL NO	PACK QTY.	DIMESION (WXHXD) MM	WEIGHT
SA-700	1	400X320X130	5.6 KG

+91-8527498960, 8527498961, 8527498962

sales@agniprotection.com, support@agniprotectionindia.com

www.agniprotection.com